

Y STRAINER CLASS 800 SCREWED END

TC611 SUS316 A351 Gr-CF8M DIN1.4408

FEATURES:

- PIPE THREAD IN ACCORDANCE: NPT, BSPT, DIN259, DIN2999, ISO 228 CLASS A
- INVESTMENT CASTING BODY
- CLASS 800 W.O.G.
- MAXIMUM WORKING TEMPERATURE 230°C
- MATERIAL:
SUS316/ASTM A351Gr-CF8M/DIN1.4408

MATERIALS LIST:

NO.	PART NAME	MATERIAL
1	BODY	CF8M
2	SCREEN	SUS304
3	GASKET	PTFE
4	CAP	CF8M
5	STOPPER	CF8
6	GASKET	PTFE

DIMENSIONS:

SIZE		L	H	D	WEIGHT Kg
DN	NPS				
8	1/4"	65	45	31	0.26
10	3/8"	65	45	31	0.23
15	1/2"	65	45	31	0.24
20	3/4"	80	53	36	0.36
25	1"	90	68	45	0.69
32	1 1/4"	105	72	50	0.86
40	1 1/2"	120	80	59	1.35
50	2"	140	97	75	2.37
65	2 1/2"	170	112	95	4.73
80	3"	195	129	113	7.26

