



VENTILAZIONE[®]/CALOR

Ventilation and ducting hose

for hot air, smoke, fumes, chemical gasses, with high temperature. Not suitable for solid materials.



| | |
|-------------------|-------------------------|
| Norm | EN ISO 1307:2008 |
| Min. temperature | -40 °C |
| Max. temperature | +120 °C |
| Temperature peak | +145 °C |
| Compound tube | Thermoplastic elastomer |
| Construction tube | Corrugated |
| Color tube | Black |
| Compound cover | Thermoplastic elastomer |
| Cover | Corrugated |
| Color cover | Black |
| Reinforcements | Steel spiral |

Article no.: 4512 Category: [Ventilation](#)

Description

Description

| Art.-no. | Ø Inner mm | Bending radius mm | Vacuum bar | Weight/mtr | Length mtr. |
|------------|------------|-------------------|------------|------------|-------------|
| 4512050000 | 51 | 50 | 0,22 | 0,220 kg | 20 |
| 4512060000 | 60 | 60 | 0,18 | 0,250 kg | 20 |
| 4512070000 | 70 | 70 | 0,15 | 0,340 kg | 20 |
| 4512075000 | 76 | 75 | 0,11 | 0,370 kg | 20 |
| 4512080000 | 80 | 80 | 0,11 | 0,390 kg | 20 |
| 4512090000 | 90 | 90 | 0,11 | 0,440 kg | 20 |
| 4512100000 | 102 | 100 | 0,1 | 0,490 kg | 15 |
| 4512110000 | 110 | 110 | 0,1 | 0,530 kg | 15 |
| 4512125000 | 127 | 127 | 0,09 | 0,700 kg | 15 |
| 4512140000 | 140 | 140 | 0,09 | 0,760 kg | 15 |
| 4512150000 | 152 | 152 | 0,07 | 0,830 kg | 15 |
| 4512160000 | 160 | 160 | 0,07 | 0,880 kg | 15 |
| 4512200000 | 203 | 203 | 0,06 | 1,230 kg | 15 |

Application: The hose is suitable for suction of hot air, smoke, gas, chemical vapors and aeration of engines. Due to the use of a high quality thermoplastic elastomer, it is extremely suitable for extraction systems where higher temperatures are released. Not suitable for solid materials.

Remark:

- Custom length possible