
REDUCING FLANGES



VIRGIN PTFE:
DN 100 – DN 250

ANTI STATIC PTF

ANTI STATIC PTFE, C4 = A : DN 100 – DN 250



DN1	DN2	ØD mm	b mm	DN1				DN2					REFERENCE															
				Ø k1 Holes			Ø k2 Holes		Type	Weight																		
				mm	nb	Ø	Bolting	mm n	nb	Bolting	Туре	kg	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15 1	6
100	15	220	45	180	8 x	18		65	4 x	M12	Α	11	D	1	-	-	В	R	-	-	-	Q	Н					
	20	220	45	180	8 x	18		75	4 x	M12	Α	11	D	1	-	-	В	R	-	-	-	Q	J					
	25	220	45	180	8 x	18		85	4 x	M12	Α	11	D	1	-	-	В	R	-	-	-	Q	K					
	32	220	45	180	8 x	18		100	4 x	M16	Α	11	D	1	-	-	В	R	-	-	-	Q	L					
	40	220	45	180	8 x	18		110	4 x	M16	Α	11	D	1	-	-	В	R	-	-	-	Q	M					
	50	220	45	180	8 x		M16	125	4 x	M16	В	10	D	1	-	-	В	R	-	-	-	Q	N					
	65	220	45	180	8 x		M16	145	4 x	M16	В	10	D	1	-	-	В	R	-	-	-	Q	0					
	80	220	45	180	8 x		M16	160	8 x	M12	С	10	D	1	-	-	В	R	-	-	-	Q	Р					
125	32	250	45	210	8 x	18		100	4 x	M16	Α	13	D	1	-	-	В	R	-	-	-	R	L					
	40	250	45	210	8 x	18		110	4 x	M16	Α	13	D	1	-	-	В	R	-	-	-	R	M					
	50	250	45	210	8 x	18		125	4 x	M16	Α	12	D	1	-	-	В	R	-	-	-	R	N					
	65	250	45	210	8 x		M16	145	4 x	M16	В	12	D	1	-	-	В	R	-	-	-	R	0					
	80	250	45	210	8 x		M16	160	8 x	M16	В	12	D	1	-	-	В	R	-	-	-	R	Р					
150	100	250	45	210	8 x		M16	180	8 x	M16	С	12	D	1	-	-	В	R	-	-	-	R	Q					
	25	285	45	240	8 x	22		85	4 x	M12		17	D	1	-	-	В	R	-	-	-	S	K					
	32	285	45	240	8 x	22		100	4 x	M16	Α	17	D	1	-	-	В	R	-	-	-	S	L					
	40	285	45	240	8 x	22		110	4 x	M16	Α	17	D	1	-	-	В	R	-	-	-	S	M					
	50	285	45	240	8 x	22		125	4 x	M16	Α	17	D	1	-	-	В	R	-	-	-	S	Ν					
	65	285	45	240	8 x	22		145	4 x	M16	Α	17	D	1	-	-	В	R	-	-	-	S	0					
	80	285	45	240	8 x	22		160	8 x	M16	Α	16	D	1	-	-	В	R	-	-	-	S	Р					
	100	285	45	240	8 x		M20	180	8 x	M16	В	15	D	1	-	-	В	R	-	-	-	S	Q					
	125	285	45	240	8 x		M20	210	8 x	M20	В	14	D	1	-	-	В	R	-	-	-	S	R					
200	25	340	45	295	8 x	22		85	4 x	M12	С	25	D	1	-	-	В	R	-	-	-	Т	K					
	32	340	45	295	8 x	22		100	4 x	M16	Α	25	D	1	-	-	В	R	-	-	-	Т	L					
	40	340	45	295	8 x	22		110	4 x	M16	Α	25	D -	1	-	-	В	R	-	-	-		M					
	50	340	45	295	8 x	22		125	4 x	M16	A	25	D	1	-	-	В	R	-	-	-	T	N					
	65	340	45	295	8 x	22		145	4 x	M16	A	25	D	1	-	-	В	R	-	-	-	T						
	80	340	45	295	8 x	22		160	8 x	M16	A	24	D	1	-	-		R	-	-	-	-	Р					
	100	340	45	295	8 x	22		180	8 x	M16	A	23	D	1	-	-	В	R	-	-	-	T						
	125	340	45	295	8 x	22	1400	210	8 x	M20	В	22	D	1	-	-		R	-	-	-	Т	R					
	150	340	45	295	8 x	00	M20			M20	В	20	D	1	-	-	В	R	-	-	-							
250	40	395	45		12 x			110	4 x	M16	A	34	D	1	-	-		R	-	-	-	U						
	50	395	45		12 x				4 x	M16	A	34	D	1	-			R	-	-	-	U						
	65	395	45		12 x			145	4 x	M16	A	34	D	1	-			R	-	-	-		0					
	80	395	45	350	12 x	22		160	8 X	M16	Α	33	D	1	-	-	В	K	-	-	-	U	Ч					