

VIRGIN PFA: DN 20 - DN 80

LINING

ANTI STATIC PFA : DN 20 – DN 80, **C4 = A**

VIRGIN PTFE: DN 100 – DN 125

ANTI STATIC PFA : DN 100 - DN 125, **C4 = A**

DN1	DN2	L1 mm	L2 mm	Weight kg	REFERENCE															
					1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
20	15	95	85	3.2	D	1	-	-	Т	R	-	-	-	J	Н	-	-	-	Т	
25	15	110	85	3.8	D	1	-	-	Т	R	-	-	-	K	Н	-	-	-	Т	
	20	110	95	4.1	D	1	-	-	Т	R	-	-	-	K	J	-	-	-	Т	
32	15	130	85	5.3	D	1	-	-	Т	R	-	-	-	L	Н	-	-	-	Т	
	20	130	95	5.6	D	1	-	-	Т	R	-	-	-	L	J	-	-	-	Т	
	25	130	110	5.9	D	1	-	-	Т	R	-	-	-	L	K	-	-	-	Т	
40	15	150	85	6.0	D	1	-	-	Т	R	-	-	-	M	Н	-	-	-	Т	
	20	150	95	6.4	D	1	-	-	Т	R	-	-	-	M	J	-	-	-	Т	
	25	150	110	6.7	D	1	-	-	Т	R	-	-	-	M	K	-	-	-	Т	
	32	150	130	7.4	D	1	-	-	Т	R	-	-	-	M	L	-	-	-	Т	
50	15	120	85	7.4	D	1	-	-	Т	R	-	-	-	N	Н	-	-	-	Т	
	20	120	95	7.8	D	1	-	-	Т	R	-	-	-	N	J	-	-	-	Т	
	25	120	110	8.0	D	1	-	-	Т	R	-	-	-	N	K	-	-	-	Т	
	32	120	130	8.7	D	1	-	-	Т	R	-	-	-	N	L	-	-	-	Т	
	40	120	150	9.1	D	1	-	-	Т	R	-	-	-	N	М	-	-	-	Т	
65	25	140	110	9.9	D	1	-	-	Т	R	-	-	-	0	K	-	-	-	Т	
	32	140	130	10	D	1	-	-	Т	R	-	-	-	0	L	-	-	-	Т	
	40	140	150	11	D	1	-	-	Т	R	-	-	-	0	M	-	-	-	Т	
	50	140	120	11	D	1	-	-	Т	R	-	-	-	0	Ν	-	-	-	Т	
80	25	165	110	12	D	1	-	-	Т	R	-	-	-	Р	K	-	-	-	Т	
	32	165	130	13	D	1	-	-	Т	R	-	-	-	Р	L	-	-	-	Т	
	40	165	150	13	D	1	-	-	Т	R	-	-	-	Р	М	-	-	-	Т	
	50	165	120	14	D	1	-	-	Т	R	-	-	-	Р	N	-	-	-	Т	
	65	165	140	15	D	1	-	-	Т	R	-	-	-	Р	0	-	-	-	Т	
100	40	205	150	16	D	1	-	-	Т	R	-	-	-	Q	M	-	-	-	M	
	50	205	120	17	D	1	-	-	Т	R	-	-	-	Q	N	-	-	-	M	
	65	205	140	18	D	1	-	-	Т	R	-	-	-	Q	0	-	-	-	M	
	80	205	165	19	D	1	-	-	Т	R	-	-	-	Q	Р	-	-	-	M	
125	40	245	150	23	D	1	-	-	Т	R	-	-	-	R	M	-	-	-	M	
	50	245	120	23	D	1	-	-	Т	R	-	-	-	R	N	-	-	-	M	
	65	245	140	24	D	1	-	-	Т	R	-	-	-	R	0	-	-	-	M	
	80	245	165	25	D	1	-	-	Т	R	-	-	-	R	Р	-	-	-	M	
	100	245	205	27	D	1	-	-	Т	R	-	-	-	R	Q	-	-	-	M	


Standard construction:

• Type K: fix flanges, DN 25 to DN 80, C13 = K


• Type P: fix flanges

On request:

• 3 loose flanges C12=3



Construction type K



Construction type P